

BÖWE AQUEOUS SB TUMBLE DRYERS

A Model of Strength, Reliability and Efficiency

BÖWE has developed a wide range of dryers that prepare garments for the final folding. Its sturdy construction, the stainless steel reversing drum, the possibility of using different heating options, electricity, steam or gas and the multiple programming possibilities allow you to find the best solution for each drying process on your laundry.



Technical Details: **AQUEOUS SB TUMBLE DRYERS**

Loading Capacities: 11, 17, 23, 27,5, 33, 45, 60, 75 KG

Heating: Electrical / Steam / Gas

- Robust grey skinplate insulated panels stainless steel Axial and radial dynamic drum

- Reversing drum action

- Dry tronic electronic control with progressive cool-down

- iDry

- Large drawer lint filter

- Double door glass

- Aqueous heat pump system

Optional: Stainless steel front panel



DRY TRONIC ELECTRONIC CONTROL

The control of BÖWE SB Tumble Dryers is easy and intuitive to use. It offers the possibility to select the required drum speed, temperatures, check the alarms and dry according to the set moisture level.



The service menu displays and monitors the statistics and the machine configuration setup.



Tumble Dryers

Capacity		Modell	Volume	Door Ø	heating kw	consumption kg/h	air exhaust kwh	air exhaust mm Ø
1:20	1:25							
11kg	8,5kg	SB-11 PSM	210	574	12,55	53	20,51	200
17	13	SB-17 PSM	330	574	18,55	53	20,51	200
23	18,5	SB-23 PSM	460	574	25,17	87	31	200
27,5	22	SB-28 PSM	550	802	31,35	87	41	200
33	26,5	SB-33 PSM	660	802	37,35	89	41	200
45	35,8	SB-45 PSM	896	1070	57	121	60	300
60	48	SB-60 PSM	1202	1355	75,35	171	90	300
75	60	SB-75 PSM	1500	1695	75,75	171	120	300

Save up to 40% of energy with the **AQUEOUS**® air recycling models



TUMBLE DRYERS

	SB-11 PSM	SB-17 PSM	SB-23 PSM	SB-28 PSM	SB-33 PSM	SB-45 PSM	SB-60 PSM	SB-75 PSM
Width (W in mm)	785	785	890	985	985	1270	1270	1270
Depth (D in mm)	840	1100	1245	1054	1210	1085	1345	1577
Height (H in mm)	1694	1694	1812	1946	1946	2380	2380	2380
Height centre door (L in mm)	976	976	1030	1040	1040	1275	1275	1275
Net weight (kg)	172	187	210	230	260	395	529	657
Packing dimension (mm)	865x940x1840	865x1210x1840	970x1345x1940	1065x1154x2080	1065x1310x2080	1330x1185x2085	1330x1445x2085	1330x1677x2085
Gross weight (kg)	180	200	230	260	285	430	575	715