



C200-260-330/51

FLATWORK DRYING IRONERS FRONT RETURN

Flatwork dryer-ironers C200-260-330/51

Front-service type to be used by one or two operators, with possibility of approaching the rotary drying press to the wall. Perfect ironing and drying thanks to NOMEX® belts winding on nearly the whole roller surface. Easy loading of laundry thanks to the laundry conveying strips allowing easy handling of the appliance. Effective width 200 ÷ 260 ÷ 330cm. Digital thermostat to select different temperatures and constant visual control of the attained temperature (only on gas and electric model). Steam models incorporate and analog thermometer for temperature control. Safety thermostat to avoid undesirable overheating (only on gas and electric models). Adjustable roller revolving speed from 0.1m/min till 9m/min through frequency controlled motor. Finger-saving fillet to protect the operator in case of wrong operation. Manual device to move the roller and to take off the laundry in case of power failure. Electronic device to start and to control the gas flame; Chrome plated cylinder on request.



Warning

Do not use gas drying-ironers in rooms where perchlore is used as well.

Electronic control ST23

ST23 control, standard on the entire gamma, manages temperature using the P.I.D. system (Proportional - Integral - Derivative).



Models C/51

		200	260	330
Usable length	mm	2000	2600	3300
Cylinder	Diameter (mm)	500	500	500
	Heated surface (m²)	3	4	5
	Speed (mt/min)	1 ÷ 8	1 ÷ 8	1 ÷ 8
Exhaust	Number	1 (2*)	2	2
	Diameter (mm)	1 x 153 (2 x 153*)	2 x 153	2 x 153
	Extraction power (m³/h)	600 (2 x 600*)	2 x 600	2 x 600
Capacity	kg/h	50 ÷ 70	60 ÷ 80	80 ÷ 120
	Water evaporation (l/h)	35 ÷ 49	42 ÷ 56	56 ÷ 84

Net and packing dimensions

Net dimensions <i>with trays</i>	Width (mm)	2810	3410	4110
	Depth (mm)	956	956	956
	Height (mm)	1189	1189	1189
Net dimensions <i>without trays</i>	Width (mm)	2810	3410	4110
	Depth (mm)	835	835	835
	Height (mm)	1189	1189	1189
Packing dimensions	Width (mm)	3010	3610	4310
	Depth (mm)	1150	1150	1150
	Height (mm)	1500	1500	1500
	Volume (m³)	5.2	6.3	7.44
Net / Gross weight	kg	925 ÷ 985	1200 ÷ 1270	1475 ÷ 1555
Noise	dB	60 (65*)	65	65

Electric heated models

Power supply	V / ph / Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz
		380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz
		440-480V 3~ 60Hz	440-480V 3~ 60Hz	440-480V 3~ 60Hz
Electric thermal power	kW	31.5	40.5	54
Motor power	kW	0.62	0.87	0.87
Total electric power	kW	32.12	41.37	54.87
Fuse	A	50 ÷ 100	63 ÷ 125	100 ÷ 160

Gas heated models*

Power supply	V / ph / Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz
		380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz
		440-480V 3~ 60Hz	440-480V 3~ 60Hz	440-480V 3~ 60Hz
Gas thermal power	kW	40	55	69
Natural gas consumption	m³/h	4.2	5.8	7.3
Liquid gas consumption	kg/h	3.1	4.3	5.6
Motors power	kW	0.87	0.87	0.87
Total electric power	kW	0.87	0.87	0.87
Fuse	A	2 ÷ 4	2 ÷ 4	2 ÷ 4

Steam heated models

Power supply	V / ph / Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz
		380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz
		440-480V 3~ 60Hz	440-480V 3~ 60Hz	440-480V 3~ 60Hz
Indirect steam pressure	kPa (bar)	1000 (10)	1000 (10)	1000 (10)
Steam consumption	kg/h	50	67	85
Motor power	kW	0.62	0.87	0.87
Total electric power	kW	0.62	0.87	0.87
Fuse	A	2 ÷ 4	2 ÷ 4	2 ÷ 4

C200-260-330/51 201607 rel.02 REF GR000000000011

The manufacturer declines all responsibility for any inexactitudes contained in this catalogue. The manufacturer reserves the right to bring, without warning, any modifications he might believe necessary, without changing the essential characteristics of the product.

grandimpianti i.l.e - Ali spa
via masiere, 211/c - 32037 sospiolo (BL) Italy
ph. +39 0437 848 711 - fax +39 0437 879 108
www.grandimpianti.com - info@grandimpianti.com



COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =
= ISO 14001 =

an Ali Group Company



The Spirit of Excellence