

BÖWE AQUEOUS BWH WASHER Extractors

A model of efficiency and quality

The new range of BÖWE washer extractors has been designed taking into account the selection of the appropriate materials and tests under the toughest working conditions. Factors such as ergonomics, easy operation, energy saving, durability and low maintenance have been decisive in the development of this range. Its sturdy stainless steel construction, the different heating options, electricity, steam or hot water, the different spin speeds and the programming possibilities help you find the best



Technical Details:

- Loading Capacities:
10KG, 13KG, 18KG, 25KG, 35KG, 45KG, 60KG, 120 KG
- Heating: Electrical / Steam

Touch-Screen with:

- 33 Languages
- USB-Port
- 26 Pre Set Programs
- Eco-Mode
- Automatic Liquid detergent Dosing Pump

The new 4.3" screen TP control is available in 33 different languages and is equipped with a USB port that allows software updates, programming and data import/export for traceability purposes. The user friendly intuitive icon programming system allows you to select from 26 pre-set programs, create new custom programs or use the economy mode cycles which provides energetic savings and reduces washing times. In the AQUEOUS@ washers the system can also be configured to run Wet Cleaning washing cycles that use independent automatic liquid detergent dosing pumps (standard 8 signals with time and delay selection). In large capacities the LAUNDRY AID features with water and rotation control help to load easily the linen and the AUTOMATIC WEIGHING SYSTEM (optional) that automatically adjusts water, soap and energy in relation to the linen load present in the machine with savings up to 30%.



- ⊕ Robust stainless steel design
- ⊕ Soft mount with imbalance control
- ⊕ Efficient water mixer
- ⊕ Standard 3 water inlets
- ⊕ Cascade drum with performed ribs
- ⊕ Efficient load system
- ⊕ Touch control with USB port
- ⊕ Electric, or steam heating


Optional: Auto Weight, tilt system, easy load plinth, double drain



Washer extractors

capacity 1:10	Ⓜ	Modell	g-factor	door Ø	heating kw	consumption kg/h	drain mm	water inlet inch	steam inlet inch
10kg	6kg	BWH-10	450	290mm	6,25	7	80	3/4"	1/2"
13	8	BWH-13		373	9,5	8,5	80	3/4"	1/2"
18	11	BWH-18		373	12,75	12	80	3/4"	1/2"
25	15	BWH-25		373	19	15	80	3/4"	3/4"
35	21	BWH-35		560	22	18	80	3/4"	3/4"
45	27	BWH-45	350	560	31,3	19	80	3/4"	3/4"
60	37	BWH-60		560	40	21	80	3/4"	3/4"
120	70	BWH-120		350	700	-	26,5	115	1-1/2"

Machine dimensions



WASHER EXTRACTORS

	BWH-10 TP	BWH-13 TP	BWH-18 TP	BWH-25 TP	BWH-35 TP	BWH-45 TP	BWH-60 TP	BWH-120 TP
Width (W in mm)	692	788	884	979	1095	1478	1836	
Depth (D in mm)	788	870	914	1041	1108	1444	1863	
Height (H in mm)	1158	1301	1409	1548	1598	1905	2245	
Height centre door (L in mm)	625	700	750	865	885	1118	1330	
Net weight (kg)	230	250	360	490	750	1350	1400	1400
Packing dimension (mm)	730x1000x1410	830x1010x1560	930x1030x1700	1040x1160x1850	1165x1230x1920	1540x1590x1970	1900x1940x2290	
Gross weight (kg)	239	283	393	545	820	1420	1520	1520